

DIGITUS Amplificador de sinal HDMI 4K

DS-55900-1
EAN 4016032370871



4K HDMI Repeater up to 30m HDMI High Speed compatible and HDCP compliant

Pretende ampliar o seu sinal HDMI sem comprometer a qualidade? É nesta situação que o repetidor HDMI atua. Os repetidores HDMI permitem que os dispositivos HDMI sejam ligados uns aos outros em grandes distâncias. O amplificador Digitus HDMI aumenta o seu sinal HDMI em até 30 metros e suporta resoluções brilhantes 4K (30 Hz) para uma excelente qualidade de imagem. Adicionalmente, a caixa compacta permite uma colocação discreta. Além disso, não exige uma fonte de alimentação externa.

Aumenta os sinais HDMI por mais 30 m

- Repetidor de sinal HDMI até 30 m
- Amplia os sinais HDMI sem qualquer perda de qualidade da imagem
- Suporta resoluções de 4 K para imagem de excelente qualidade
- Caixa pequena e compacta - perfeita para uma colocação discreta

- Não é necessária fonte de alimentação externa
- Resolução de vídeo até 4 K (4K2K@24 Hz)
- Suporta 3D
- Largura da banda: 3,4Gbps
- Profundidade de cor: até 16 bit a uma resolução de 1080 pixéis
- Dimensões: C 4,8 x L 2,6 x A 1,4 cm
- Cor: preto

Attributes

- HDTV Standard: Ultra HD 4K
- Distance: 30 m
- KVM: no
- PoE (Power over Ethernet): no

Package contents

- Repetidor HDMI
- GIR (Guia Instalação Rápida)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	7.76	61.00	26.00	39.00	61,854.00
Packaging Unit Inside	20	0.78	25.00	12.00	17.00	5,100.00
Packaging Unit Single	1	0.04	11.80	7.50	2.30	203.55
Net single without Packaging	1	0.02	2.60	4.70	1.70	0.00

More images:





VIDEO VERLÄNGERUNGEN
VIDEO EXTENSIONS

M = Meter / meters

HDMI	
DS-55900-1 (up to 1080p)	50 M
DS-55901	50 M
DS-55100	50 M
DS-55400 (up to 1080p) (HDMI)	50 M / 100 M
DS-55500 (HDMI)	100 M
DS-55100	50 M

VGA	
DS-55900-1	50 M
DS-55500 (HDMI)	100 M
DS-55400	50 M
DS-55400 (EXTENDED RANGE) (HDMI)	50 M
DS-55400 (EXTENDED RANGE) (HDMI)	50 M

DVI	
DS-54901	50 M
DS-54101	25 M

HDMI EXTENDER LÖSUNGEN
HDMI EXTENDER SOLUTIONS



HDMI Cables





Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com