

# **DIGITUS Fiber Optic Multimode Patch Cord, LC / LC**

DK-2533-02-5 EAN 4016032424512





### FO patch cord, duplex, LC to LC MM OM5 50/125 æ, 2 m $\,$

FO patch cord, duplex, LC to LC,MM OM5 50/125  $\mu$ , 2 m

# Melhor desempenho e melhor qualidade de ligação com a rede.

• LSOH

## **Attributes**

- Assortment: Fiber Optic Patch Cables
- Boot: single-color
- · Cable diameter: 2 mm

- Cable type: I-VH 2G50/125μ
- Color cable: lemon green
- Connector 1: LC
- Connector 2: LCFiber class: OM5
- Fiber diameter: 50/125µ
- Mode: Multimode
- Packaging: DIGITUS Polybag
- Length: 2 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	160	8.00	35.00	30.00	45.00	47,250.00
Packaging Unit Inside	10	0.50	12.00	30.00	35.00	12,600.00
Packaging Unit Single	1	0.05	1.50	20.00	27.00	810.00
Net single without Packaging	1	0.05	0.00	0.00	0.00	0.00


## More images:











#### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- · eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect
  against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- · To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
  operating temperature of the cable
- · Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com