

# DIGITUS Cabo de ligação DisplayPort

**AK-340106-010-S**  
**EAN 4016032450320**



**DisplayPort connection cable, DP M/M, 1.0m,w/lock, UHD 8K, Vers. 1.3/1.4, bl**

Este cabo HD áudio/vídeo digital de elevado desempenho serve para a ligação de computadores ou computadores portáteis a monitores com interface DisplayPort.

**Ideal para CAD/CAM, GIS, desenvolvimento 3D, simulação em tempo real e mais.**

- Taxa de transferência: até 32,4 GBit/s
- Suporta resoluções até 4K/2K@120 Hz (Ultra HD)
- Suporta resoluções até 5K@60 Hz (Ultra HD)
- Suporta resoluções até 8K@30 Hz (Ultra HD)
- Resolução de vídeo suportada: 7680 x 4320 dpi; 5120 x 2880 dpi; 3840 x 2160 dpi
- Profundidade de cor: 24 bit RGB
- Suporta 1-8 canais de áudio para transmissão de áudio

- Frequências de amostragem de áudio: 32-192 kHz com taxa de bits máx. de 4.608 kB/s
- Suporta HDCP e DPCP
- Instalação Plug & Play

**Attributes**

- Color cable: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.4
- HDTV Resolution max.: 7680 x 4320 Pixel, 60Hz
- HDTV Standard: Ultra HD 8K
- Length: 1 m
- AOC - Active Optical Cable: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	100	8.00	50.00	33.00	22.00	36,300.00
Packaging Unit Inside	5	0.40	15.00	8.00	22.00	2,640.00
Packaging Unit Single	1	0.08	12.00	1.50	14.50	261.00
Net single without Packaging	1	0.06	14.00	12.50	2.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)