

# DIGITUS Wall-mounted housing 254 mm (10") - 312x300 mm (WxD)

DN-10-09U-B  
EAN 4016032473985



## 254 mm (10") 9U wall mounting cabinet 464x312x300 mm, color black (RAL 9005)

Whether in the home, office or in sub-distribution boards where space is limited: With the compact 254 mm (10") solutions, you can install your network wherever you want. Available in three height units (6U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry with brushes in the top and bottom. A pair of galvanized 254 mm (10") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). Door hinges can be changed. Furthermore, the cabinets can be completely dismantled if required thanks to the demountable design.

**As caixas de parede DIGITUS® foram concebidas, preparadas e desenvolvidas para as elevadas exigências das infraestruturas de TI.**

- Classe de proteção IP20
- Porta com vidro de segurança com fecho
- Ângulo de abertura de porta de 200°
- Dispositivo de bloqueio de 1 ponto na porta frontal

- Folha de aço robusta 1,1 - 1,5 com elevada capacidade de carga, pintada por pulverização
- Entrada de cabo com faixa de escova no telhado e com tampa de plástico no pavimento
- Ranhuras de ventilação para ventilação e saída ativa e passiva
- Incluindo parafuso de aterramento na parte inferior da caixa

### Attributes

- Cabinet type: Wall mounting cabinet
- Color: black, RAL 9005
- Depth: 300 mm
- Front door: Glass door, single opening
- Load capacity: 30 kg
- Side panels: Both sides
- Units: 9
- Width: 312 mm
- IP protection class: IP20
- Mounted: yes

### Package contents

- Installation set (screws, cage nuts, washers)
- 2x key

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 1            | 10.00       | 36.00      | 37.00      | 52.00       | 69,264.00 |
| Packaging Unit Inside        | 1            | 10.00       | 36.00      | 37.00      | 52.00       | 69,264.00 |
| Packaging Unit Single        | 1            | 10.00       | 36.00      | 37.00      | 52.00       | 69,264.00 |
| Net single without Packaging | 1            | 8.70        | 30.00      | 31.20      | 46.40       | 0.00      |

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)