

# DIGITUS 10Gb/s SFP+SR MM 850nm 300m DDM Industrial

DN-81212  
EAN 4016032476948



### 10G SFP+SR 850nm 300m LC DDM Industrial 300m LC DDM Industrial

The 10Gb/s industrial SFP+ module allows network connectivity in industrial environments. The range of up to 300m and the wide temperature range of -40 °C up to 85°C with a power consumption of < 1W make the DN-81212 SFP+ a reliable transceiver in harsh environments.

### 10Gb/s SFP+SR MM Module 850nm 300m DDM Industrial grade

- SFP+ package with LC connector
- 850nm VCSEL Laser and PIN photo detector
- Up to 300m transmission on 2000MHz-km MMF
- Up to 11.3Gbps Data Links

- Power dissipation < 1W
- LVPECL compatible data input/output interface
- Low EMI and excellent ESD protection
- laser safety standard IEC-60825 compliant
- Compatible with SFF8472
- Operating temperature: -40 ~ 85 ° C
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik , ENTERASYS, RIVERSTONE , Unifi, Ubiquiti, ZyXEL, ZTE
- DDM Support: no

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 240          | 10.00       | 40.00      | 56.00      | 26.00       | 58,240.00       |
| Packaging Unit Inside        | 1            | 0.04        | 0.00       | 0.00       | 0.00        | 0.00            |
| Packaging Unit Single        | 1            | 0.04        | 9.30       | 11.70      | 3.20        | 348.19          |
| Net single without Packaging | 1            | 0.03        | 1.40       | 5.80       | 1.10        | 0.00            |

### More images:

