

DIGITUS Wireless HDMI KVM Extender Set, 200 m

DS-55321
EAN 4016032478812



Wireless HDMI KVM Extender Set 200 m, Full HD

The Wireless HDMI® KVM Extender Set transfers your HDMI® video and audio signals in Full HD without a cable over a distance of up to 200 m (unobstructed view). Thanks to KVM functionality, the mouse/keyboard can be connected to the receiver unit, which makes it possible to control the signal source directly on the output device. Using the HDMI loop-out to the transmitter unit, a local monitor can be connected in order to control the output to the receiver. The auto-pairing function ensures straightforward installation.

Wirelessly transmits HDMI video and audio signals in Full HD over a distance of up to 200 m with an unobstructed view and offers KVM functionality

- Wireless HDMI signal transmission up to 200 m (unobstructed view)
- Supports transmission resolutions up to 1920x1080p
- Wireless channel: IEEE 802.11ac, 5 GHz, 2T2R
- Authentication protocol: WPA2 (WPAS-PSK / WPA2-Enterprise)
- Transmitter unit connections:
 - 1x HDMI input (signal source, 4K/60Hz)
 - 1x HDMI loop-out / output
 - 1x Micro USB input (power supply, DC 5V/1A)
- 1 x IR output - Connection of IR transmitter for control of signal source
- 1x Micro USB input - Data connection of source for use of KVM function
- Receiver unit connections:

- 1x HDMI output (output device, 1080p/60Hz)
- 1x USB-A input (connection of mouse/keyboard)
- 1x Micro USB input (power supply, DC 5V/1A)
- 1x Reset button
- Power consumption: 2.5W
- Operating temperature: 0-40 °C
- Dimensions (1 unit): L 7.9 x W 15.5 x H 2.2 cm
- Weight (1 unit): 326 g
- Color: Black
- The transmission distance with a restricted visual range cannot be determined generally and depends on the specific circumstances where installed.
- Walls, glass etc. shorten the signal range or cause signal losses.
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Distance: 200 m
- KVM: yes
- PoE (Power over Ethernet): no
- Video connection ports: HDMI

Package contents

- 1x Transmitter unit
- 1x Transmitter unit
- 1x Receiver unit
- 2x Power adapter (DC 5V/1A, 0.75 m)
- 1x IR transmitter (1.5 m)
- 1x Micro USB - USB-A cable (0.5 m)
- 1x User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	11.60	26.00	34.00	47.00	41,548.00
Packaging Unit Inside	1	1.16	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.16	25.00	23.00	6.60	3,795.00
Net single without Packaging	1	0.33	7.90	15.50	2.20	0.00

More images:

