


DIGITUS CAT 5e SF/UTP патч-кабель

DK-1532-020/B
EAN 4016032199748



CAT 5e SF-UTP patch cord, PVC AWG 26/7, length 2 m, color blue

The DIGITUS® Category 5e Class D patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 5e specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 5e cabling. The performance is tested up to 100 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 5e, because of the transparent blue colored connector.

Отличная производительность и качество связи для Вашей сети.

- 2 разъема RJ45 (8P8C)
- Колпачки с защитой от излома, натяжения и перегиба
- Метки длины на оболочке
- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 5e
- Shielding: SF-UTP, foil and braid shielding
- Length: 2 m
- Color: blue
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 150 | 9.70 | 46.00 | 33.00 | 28.00 | 42,504.00 |
| Packaging Unit Inside | 10 | 0.65 | 7.50 | 25.00 | 42.00 | 7,875.00 |
| Packaging Unit Single | 1 | 0.06 | 1.50 | 14.00 | 25.00 | 525.00 |
| Net single without Packaging | 1 | 0.07 | 200.00 | 1.20 | 1.30 | 0.00 |