


DIGITUS CAT 5e SF/UTP patch cord

DK-1532-150/R EAN 4016032199878





CAT 5e SF-UTP patch cable, PVC AWG 26/7, length 15 m, color red

The DIGITUS® Category 5e Class D patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 5e specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 5e cabling. The performance is tested up to 100 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 5e, because of the transparent blue colored connector.

Future-oriented standards and high-end quality for your network

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot

Attributes

- · Configuration: 1:1
- Category: CAT 5e
- Shielding: SF-UTP, foil and braid shielding
- Length: 15 m
- · Color: red
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair
- · Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	25	11.00	37.00	37.00	27.00	36,963.00
Packaging Unit Inside	5	2.20	46.00	32.00	19.00	27,968.00
Packaging Unit Single	1	0.44	4.00	23.00	28.00	2,576.00
Net single without Packaging	1	0.44	0.00	0.00	0.00	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Ensure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.



EU responsible person

EU based economic operator ensuring the product complies with the required regulations. ASSMANN Electronic GmbH Auf dem Schüffel 3 $\,$

Lüdenscheid, Germany https://www.assmann.com info@assmann.com