

DIGITUS Wall Mounting Cabinets IP55 - Outdoor - 600x450 mm (WxD)

DN-19 16U-I-OD
EAN 4016032362128



16U wall mounting cabinet, outdoor, IP55 891x600x450 mm, color grey (RAL 7035)

The industrial network cabinets for wall installation are specially adapted according to protection type IP55 for the requirements of harsh environments, particularly outdoors. The wall housings offer optimal performance in part thanks to the 3-point locking system with lockable swing handle and insulated PG cable glands. Integrated fan filter housing ensures fresh air supply (protection against penetration of water and dust pursuant to IP54). Applications including outdoor areas that are subject to environmental effects (rain, dust, hail, snow, spraying water). To accommodate a fan module, the roof structure is also equipped with a filtered area. One pair (two pairs starting from a depth of 600 mm) of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth can be adjusted. Each cabinet is made of up to 2.0 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard color gray (RAL 7035). Wall installation is carried out using the enclosed mounting bracket. Optionally, the cabinets can be used with a plinth as a free-standing solution or fastened to poles using the fastening set.

The DIGITUS® IP55 Outdoor Wall Mounting Cabinets are designed for industrial applications with protection against water and dust acc. to safety class IP55.

- Профильные направляющие 483 мм (19") установлены на передней стороне внутри шкафа, гальванизированы
- Профильные направляющие 483 мм (19") регулируются по глубине установки и имеют маркировку высоты в монтажных единицах
- прочный 1.5 мм стальной лист с высокой нагрузочной способностью, окрашенный порошковой краской
- Cabinet type: Wall mounting cabinet, outdoor
- Color: light grey, RAL 7035
- Depth: 450 mm
- Front door: Steel door, closed, single opening
- Load capacity: 100 kg
- Units: 16
- Width: 600 mm
- IP protection class: IP55
- Mounted: no

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	42.00	50.00	65.00	94.10	305,825.00
Packaging Unit Inside	1	42.00	50.00	65.00	94.10	305,825.00
Packaging Unit Single	1	42.00	50.00	65.00	94.10	305,825.00
Net single without Packaging	1	41.00	45.00	60.00	89.10	0.00

More images:

