


DIGITUS CAT 8.2 S/FTP installation cable, 500 m, Simplex, Dca-s2,d1,a1

DK-1843-VH-5
EAN 4016032380542



CAT 8.2 S-FTP install. cable, 2000 MHz, AWG 22/1 Dca, 500 m, drum, simplex, yellow

The Digitus Cat 8.2 S/FTP installation cable is designed for use in the structured data center and the building cabling according to ISO/IEC 11801, DIN EN 50288-12-1, DIN EN 50173, IEC 60332-3-24. The cable is perfectly suitable for the transmission of both analog and digital data and also supports POE. The shielding structure is composed of single shielded pairs with a tinned copper braid, which ensures excellent shielding and electrical values.

Future-oriented standards and high-end quality for your network

- Physical properties:
- Conductor: Bare annealed copper, solid AWG 22/1
- System/s of AVCP: AVCP 3
- Insulation: SFS-PE (foamed polyethylene sheath)
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Shielding of the individual pairs: Aluminum-covered polyester film, 100% coverage
- Overall shielding: Tinned copper wire braid
- Outer sheath: Dca acc. to EN 50575; LSZH
- Outer sheath diameter (nominal): 0.55 mm nominal
- Outer sheath color: Green
- Mechanical properties:
- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Transport and storage temperature range: -20 °C to +75 °C
- Operating temperature range: -20 °C bis +60 °C






- Installation temperature range: 0 °C to +50 °C
- Overall diameter Simplex (nominal): 7.9 mm nominal (Dca)
- Weight (kg/km): 65 kg/km
- Electrical properties:
- Impedance: 100±15 Ohm @ 1 - 2000MHz
- Capacitance: 99 pF/30m nominal @ 1 KHz
- Capacitance unbalance (pair-ground): Is not specified
- Insulation resistance: 5 GOhm x km min.
- DC resistance: 2.4Ohm/30m max. (4% max. resistance unbalance)
- DC loop resistance: 5.6 Ohm/24m max. (3% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: CA-Type 1
- Signal propagation delay: 171 nS/30 m max.
- Propagation delay: 13,5 nS/130 m max.
- Separating class: „d“ acc. to EN 50174-2
- NVP: 79%
- Assortment: Twisted Pair Installation Cables
- Category: CAT 8.2
- Category: CAT 8.2
- Shielding: S-FTP, pairs in metal foil and braid shielding
- CPR: Dca
- Length: 500 m
- Color: green
- Jacket: LSOH
- Structure: 4 x 2 AWG 22/1, solid twisted pair

Package contents

- CAT 8.2 S/FTP installation cable on drum, 500 m, Simplex, Dca

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	30.00	34.00	39.50	39.50	53,048.50
Packaging Unit Inside	1	30.00	34.00	39.50	39.50	53,048.50
Packaging Unit Single	1	30.00	34.00	39.50	39.50	53,048.50
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Produktinformation Product Information	Physikalische Spezifikationen Physical Properties
Bezeichnung: CAT 8.2 S/FTP Installation Cable, 500m, Simplex, D _{ca}	Standard: IEC 61905-1-10, IEC 61905-1-11, IEC 61905-1-12, IEC 61905-1-13, IEC 61905-1-14, IEC 61905-1-15, IEC 61905-1-16, IEC 61905-1-17, IEC 61905-1-18, IEC 61905-1-19, IEC 61905-1-20, IEC 61905-1-21, IEC 61905-1-22, IEC 61905-1-23, IEC 61905-1-24, IEC 61905-1-25, IEC 61905-1-26, IEC 61905-1-27, IEC 61905-1-28, IEC 61905-1-29, IEC 61905-1-30, IEC 61905-1-31, IEC 61905-1-32, IEC 61905-1-33, IEC 61905-1-34, IEC 61905-1-35, IEC 61905-1-36, IEC 61905-1-37, IEC 61905-1-38, IEC 61905-1-39, IEC 61905-1-40, IEC 61905-1-41, IEC 61905-1-42, IEC 61905-1-43, IEC 61905-1-44, IEC 61905-1-45, IEC 61905-1-46, IEC 61905-1-47, IEC 61905-1-48, IEC 61905-1-49, IEC 61905-1-50, IEC 61905-1-51, IEC 61905-1-52, IEC 61905-1-53, IEC 61905-1-54, IEC 61905-1-55, IEC 61905-1-56, IEC 61905-1-57, IEC 61905-1-58, IEC 61905-1-59, IEC 61905-1-60, IEC 61905-1-61, IEC 61905-1-62, IEC 61905-1-63, IEC 61905-1-64, IEC 61905-1-65, IEC 61905-1-66, IEC 61905-1-67, IEC 61905-1-68, IEC 61905-1-69, IEC 61905-1-70, IEC 61905-1-71, IEC 61905-1-72, IEC 61905-1-73, IEC 61905-1-74, IEC 61905-1-75, IEC 61905-1-76, IEC 61905-1-77, IEC 61905-1-78, IEC 61905-1-79, IEC 61905-1-80, IEC 61905-1-81, IEC 61905-1-82, IEC 61905-1-83, IEC 61905-1-84, IEC 61905-1-85, IEC 61905-1-86, IEC 61905-1-87, IEC 61905-1-88, IEC 61905-1-89, IEC 61905-1-90, IEC 61905-1-91, IEC 61905-1-92, IEC 61905-1-93, IEC 61905-1-94, IEC 61905-1-95, IEC 61905-1-96, IEC 61905-1-97, IEC 61905-1-98, IEC 61905-1-99, IEC 61905-1-100

Leitungsgruppen Transmission Properties	100m	150m	200m	250m	300m	350m	400m	450m	500m
1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5
6	6	6	6	6	6	6	6	6	6
7	7	7	7	7	7	7	7	7	7
8	8	8	8	8	8	8	8	8	8
9	9	9	9	9	9	9	9	9	9
10	10	10	10	10	10	10	10	10	10

