

1

DIGITUS CAT 6A S/FTP patch cord

DK-1644-A-015 EAN 4016032423959





CAT 6A S-FTP patch cable, Cu, LSZH AWG 26/7, length 1.5 m, color grey $% \left({{\left[{{{\rm{S}}_{\rm{T}}} \right]}_{\rm{T}}} \right)$

The DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Configuration: 1:1
- Category: CAT 6A
- · Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: 1.5 m
- Color: grey
- Jacket: LSOH
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	150	9.00	46.00	33.00	28.00	42,504.00
Packaging Unit Inside	20	1.20	6.00	20.00	36.00	4,320.00
Packaging Unit Single	1	0.06	1.00	14.00	14.00	196.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:





