

# DIGITUS QSFP+ 40G 3 m DAC cable

DN-81309

EAN 4016032464297



## QSFP+ 40G 3m DAC cable

**Allnet, CISCO, D-Link, Edimax, Etherwan, Fortinet**

The DIGITUS® 40G QSFP+ DAC cables are a high-performance, low-power short-range connection solution. They are compliant with the QSFP MSA and IEEE P802.3ba. It uses 4 full duplex channels, with each channel capable of transmitting data at speeds of up to 10.3Gb/s, giving an aggregate rate of 41.2Gb/s. The DIGITUS® 40G QSFP+DAC cables offer increased port density and cost savings in the overall system.

### High bandwidth without delays or signal loss

- 3 m maximum distance
- 2.125-41.2 Gbps supported data rate
- Supported applications: 12.5G fibre channel, 10G fibre channel, 8G fibre channel, 4G fibre channel and 2G fibre channel

- Compatible brands: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL
- DDM/DOM support
- Temperature range: 0 to +70 °C
- Connectors: QSFP
- Power: +3.3 V supply voltage
- Power consumption: <1.5 W
- 850 nm wavelength multimode fibre

### Attributes

- DDM Support: no

### Package contents

- QSFP+ 40G 3 m DAC cable
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	1.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.01	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.01	26.00	26.00	2.00	1,352.00
Net single without Packaging	1	0.15	11.00	1.80	1.30	0.00

## Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

[info@assmann.com](mailto:info@assmann.com)