


# DIGITUS Adapter Plate for Fiber Optic Unibox for wall mounting, medium

DN-96802M-2  
EAN 4016032466154



**Adapter plate for DN-96800M-2, grey (RAL 7035) 12x SC-DX, LC-QD**

The adapter plate for the fiber optic Unibox is used to mount couplings that allow for the redistribution and forwarding of fiber optic cables. It can be easily stuck onto the threaded screw of the Unibox and screwed tight with the lock nut.

**Compact mount for fiber optic couplings**



- Coloring with powder coating in gray (RAL 7035)
- Product dimensions (H x W x D): 45 x 275 x 15 mm
- Weight: 0.16 kg (net); 0.17 kg (gross)

**Package contents**

- 1x adapter plate

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	15	3.00	47.00	16.00	16.00	12,032.00
Packaging Unit Inside	1	0.20	46.50	15.50	15.50	11,171.60
Packaging Unit Single	1	0.20	46.50	15.50	15.50	11,171.60
Net single without Packaging	1	0.16	27.60	1.50	4.70	0.00

**More images:**



**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.

- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)