

# DIGITUS 3-in-1 charging cable

**DB-300160-002-S**  
**EAN 4016032466208**



## USB charger cable, 0.15m 3 in 1 cable, nylon braid, black

The DIGITUS® 3-in-1 charging cable is ideal for charging your portable devices on a power supply, PC or other device with a USB-A port. Use a single cable to charge all your devices. Its compact dimensions make this cable an ideal companion for home, office or travel.

### 3-in-1 multi-charging cable for connecting devices with a USB-C, micro-USB or 8-pin connector to a USB-A port

- Supported charging power: 10 W (5 V / 2 A)
- Operating temperature: -10 °C to +50 °C
- Operating humidity: 0 - 75%
- Port 1: USB-A, male

- Connector 2: Apple, male/ □Micro-USB, male/ □USB-C, male

### Attributes

- AWG: 30
- Color cable: black
- Connector 1: USB A, plug
- Connector surface: nickel-plated
- Hoods: Metallic housing
- Wire material: CU
- Length: 0.15 m
- Shielding: Unshielded
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	7.50	29.00	55.00	20.00	31,900.00
Packaging Unit Inside	10	1.88	26.50	27.50	9.00	6,558.75
Packaging Unit Single	1	0.19	8.50	23.50	2.00	399.50
Net single without Packaging	1	0.03	46.80	15.00	0.30	0.00

## More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)