DIGITUS Wireless HDMI KVM Extender Set, 200 m

DS-55321 EAN 4016032478812



Wireless HDMI KVM Extender Set 200 m, Full HD


The Wireless HDMI® KVM Extender Set transfers your HDMI® video and audio signals in Full HD without a cable over a distance of up to 200 m (unobstructed view). Thanks to KVM functionality, the mouse/keyboard can be connected to the receiver unit, which makes it possible to control the signal source directly on the output device. Using the HDMI loop-out to the transmitter unit, a local monitor can be connected in order to control the output to the receiver. The auto-pairing function ensures straightforward installation.

Wirelessly transmits HDMI video and audio signals in Full HD over a distance of up to 200 m with an unobstructed view and offers KVM functionality

- Wireless HDMI signal transmission up to 200 m (unobstructed view)
- Supports transmission resolutions up to 1920x1080p
- Wireless channel: IEEE 802.11ac, 5 GHz, 2T2R
- Authentication protocol: WPA2 (WPAS-PSK / WPA2-Enterprise)
- Transmitter unit connections:
- 1x HDMI input (signal source, 4K/60Hz)
- 1x HDMI loop-out / output
- 1x Micro USB input (power supply, DC 5V/1A)
- 1 x IR output Connection of IR transmitter for control of signal source
- 1x Micro USB input Data connection of source for use of KVM function
- Receiver unit connections:

. . .

1x HDMI output (output device, 1080p/60Hz)



- 1x Micro USB input (power supply, DC 5V/1A)
- 1x Reset button
- Power consumption: 2.5W
- Operating temperature: 0-40 °C
- Dimensions (1 unit): L 7.9 x W 15.5 x H 2.2 cm
- Weight (1 unit): 326 g
- · Color: Black
- The transmission distance with a restricted visual range cannot be determined generally and depends on the specific circumstances where installed.
- Walls, glass etc. shorten the signal range or cause signal losses.

1

Attributes

- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Distance: 200 m
- KVM: yes
- PoE (Power over Ethernet): no
- Video connection ports: HDMI

Package contents

- 1x transmitter unit
- 1x receiver unit
- 2x power supply unit (DC 5V/1A, 0.75 m)
- 1x IR transmitter (1.5 m)
- 3x Micro USB USB-A cable (0.5 m)
- 1x operating instructions
- 2x HDMI cable (1.5m)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	11.60	26.00	34.00	47.00	41,548.00
Packaging Unit Inside	1	1.16	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.16	25.00	23.00	6.60	3,795.00
Net single without Packaging	1	0.33	7.90	15.50	2.20	0.00

www.digitus.info Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

DIGITUS®

More images:



Safety notes

- Please read these instructions carefully before using the appliance and keep them for future reference.
- For indoor use only.
- Do not use the device in a damp environment or near water.
- Do not expose the product to extremely high or low temperatures, strong light sources or direct sunlight.
- This product is not a toy. Keep it out of the reach of children.
- Do not connect the adapter to the mains until you have made sure that the mains voltage corresponds to the value specified on the rating plate.
- Never connect the power supply unit if it is damaged. In such cases, please contact your supplier.
- Disconnect the AC/DC mains adapter from the power supply if the appliance is not to be used for a longer period of time.
- Never open the product: The appliance may contain parts with lethal voltage. Repairs or maintenance should only be carried out by qualified personnel.



- Improper use, modifications or repairs carried out by the user will invalidate all warranties.
 We accept no product responsibility for improper or non-intended use of the product.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com