

# DIGITUS 4K HDMI Switch, 4x1

DS-45329

EAN 4016032480006



## 4K HDMI Switch, 4x1 4K/60Hz, 18 Gbps, HDR, HDCP 2.2, CEC

The DIGITUS® 4K HDMI Switch, 4x1 offers additional HDMI connections for your output display - 4 signal sources can be connected using just 1 HDMI connection on the screen. The video changeover switch does not require an external power adapter and is supplied with power via the Micro USB cable, e.g. via the source device. Switch conveniently between the signal sources via remote control or on the device itself.

### Extend your TV/monitor with additional HDMI connections - Switch conveniently between the signal sources without replugging

- Switch conveniently between 4 signal sources via remote control or on the device itself
- Additional HDMI connections for your output device - 4 signal sources via just 1 HDMI connection on the screen
- Power supply via Micro USB cable (included) - No external power adapter required
- Supports 4K2K/60Hz (HDR, 4:4:4)
- Video bandwidth: 18 Gbps
- Supports High Dynamic Range (HDR)

- Supports CEC (Consumer Electronics Control)
- Connections:
  - 4x HDMI input (4K/60Hz)
  - 1x HDMI output (4K/60Hz)
  - 1x Micro USB input - Power supply
- 5x Status LEDs
- 1x Changeover switch signal source
- 1 x IR receiver
- Operating temperature: 0-50°
- Power consumption: approx. 5W
- Housing: ABS
- Dimensions (housing): L 5.9 x W 13.3 x H 1.6 cm
- Weight: 80 g
- Color: black

### Package contents

- 1x HDMI Switch
- 1x Remote control
- 1x Micro USB cable (0.5 m)
- 1x QIG

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 100          | 16.00       | 53.00      | 55.50      | 33.50       | 98,540.20 |
| Packaging Unit Inside        | 1            | 0.16        | 0.00       | 0.00       | 0.00        | 0.00      |
| Packaging Unit Single        | 1            | 0.16        | 16.00      | 10.70      | 5.00        | 856.00    |
| Net single without Packaging | 1            | 0.08        | 13.30      | 5.90       | 1.70        | 0.00      |

# More images:



## Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

## EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)