

PLANET Industrial 8 Port Gigabit PoE Switch, Managed, 2 Uplinks

IGS-10020HPT
EAN 4711213689116



Planet Industrial POE+ Switch, 8xRJ45 Gigabit, 2xSFP, -40/+75°C, Managed, 240W

8 Port Gigabit Ethernet Switch, current V3 is ECE (E-Mark) certified. IP30 Industrial enclosure for DIN rail mounting, also suitable for wall mounting, 8 x 10/100/1000 Mbps (RJ45) with PoE+ Injector 802.3at (max. 36W per port), compatible with 802.3af, PoE Budget max. 252W (depending on power supply unit), 2 x SFP slots 100/1000 Mbps (for MFB and MGB modules), 2xDI/2xDO, operating temperature -40 to +75°C, ESD/EFT protection 6000VDC, power consumption max. 218 Watt (with full PoE load), redundant power inputs 12-48V DC, delivery without power supply unit. Extensive features such as Modbus TCP, VLAN, LACP, Redundant Ring (ERPS, STP, RSTP, MSTP), QoS, Multicast, IGMP Snooping, Static Layer 3 Routing, ACL and much more. Web/Telnet/Console Management, IPv4/IPv6, SNMP. Weight 1096g, dimensions 72 x 107x 152 mm.

Наилучшее решение для сложных окружающих условий!

- RJ-45 последовательный интерфейс консоли для базового управления коммутатором и настройки
- Автоопределение подключенного устройства (PD)
- Защита от короткого замыкания
- Удаленное питание на расстоянии до 100 м
- Диапазон рабочих температур от -40 до 75 °C
- Number of ports: 8
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: yes
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	1.40	13.00	7.00	2.00	182.00
Packaging Unit Inside	1	1.40	13.00	7.00	2.00	182.00
Packaging Unit Single	1	1.40	13.00	7.00	2.00	182.00
Net single without Packaging	1	1.40	13.00	7.00	2.00	0.00

More images:

