DIGITUS Gigabit Media Converter, RJ45 / SC

DN-82121-1
EAN 4016032293132



Gigabit Ethernet Media Converter, Singlemode SC connector, 1310nm, up to 20km

The media converters from DIGITUS® are the ideal solution for the migration of copper and fiber network signals. From now on, you are able to access the fiber technology and transfer network signals over several kilometers without renewing your whole network infrastructure. The huge variety of products fulfil your individual needs. The intiutive operation guarantees a quick and easy installation.

The perfect converter solution for various fiber media

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- 10/100/1000Base-TX to 1000Base-LX
- Connectors: 1x RJ45, 1x SC duplex
- Distance up to 20km
- Wavelength: 1310nm
- Singlemode Dual Fiber
- Automatic cable detection - auto MDI / MDI-X function
- Auto-negotiation of full- and half-duplex
- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Suitable for 9/125µm Fiber Cables
- Transmission Power: Minimum -12 dBm, Maximum -6 dBm
- Sensitivity Receiving Power: Minimum -21 dBm
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet, IEEE 802.3z Gigabit Ethernet
- 2MB Data Buffer
- Operating Temperature: 0 to 60°C
- Dimensions (L x W x H): 95mm x 70mm x 26mm
- Weight: 200g
- Standalone Converter with external power supply
- Input Supply Voltage: 5V DC
- Connector 1: RJ45
- Connector 2: SC
- Mode: Singlemode
- Distance (km): 20
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: no
- Ethernet speed: Gigabit

Package contents

- Media Converter
- Quick installation guide
- Power adapter


Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	9.00	30.00	27.00	55.00	44,550.00
Packaging Unit Inside	1	0.45	6.00	21.60	16.10	2,086.56
Packaging Unit Single	1	0.45	6.00	21.60	16.10	2,086.56
Net single without Packaging	1	0.18	12.00	7.00	2.60	0.00


More images:





Media Converter
DIGITUS
DC 5V
This device complies with Part 15 of the FCC rules.


DC 5V
This device complies with Part 15 of the FCC rules.


PWR 1000M
Link /Act
SD
FDX COL
TX
RX
FP
TP
UTP


PWR 1000M
Link /Act
SD
FDX COL
TX
RX
FP
TP
UTP


Media Converter