

DIGITUS mini GBIC (SFP) Module, 1.25 Gbps, 20km

DN-81001

EAN 4016032305668



1.25 Gbps SFP Module, Singlemode LC Duplex Connector, 1310nm, up to 20km

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Duplex
- 1000Base-LX - For Long Haul
- Wavelength: 1310nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity receiving power: minimum -24 dBm
- For a Distance of up to 20km
- Suitable for 09/125µm Singlemode Fiber Cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Mode: Singlemode
- Connector: LC
- Distance (km): 20
- Wavelength: 1310 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	9.00	12.00	3.00	324.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:

SFP Modules						
Product Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature
250-0101	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0102	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0103	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0104	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0105	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0106	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0107	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0108	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0109	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0110	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0111	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0112	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0113	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0114	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0115	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0116	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0117	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0118	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0119	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0120	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0121	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0122	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0123	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0124	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0125	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0126	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0127	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0128	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0129	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0130	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0131	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0132	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0133	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0134	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0135	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0136	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0137	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0138	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0139	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0140	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0141	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0142	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0143	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0144	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0145	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0146	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0147	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0148	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C
250-0149	40 Gbps	100 Gbps	10 km	LC Duplex	1310 nm	0 to 70 °C
250-0150	40 Gbps	100 Gbps	10 km	LC Duplex	1550 nm	0 to 70 °C

