

DIGITUS Industrial Network Cabinet, Indoor, IP55

DN-19 24U-I-6/6-1
EAN 4016032380665



***24U network rack, indoor IP55 1300x600x600 mm, incl. plinth, grey (RAL 7035) 1300x600x600 mm, incl. plinth, grey (RAL 7035)**

The 483 mm (19") industrial cabinets are protected against dust and water ingress acc. to safety level IP55 (IEC EN 60529) to offer optimized conditions for the user friendly installation of active- and passive network components accompanied by a neat cable management in an industrial area. The color is created by a 70-90 µ strong powder coating in color grey (RAL 7035) with an adhesion capability acc. to EN ISO 2409: Class 0 to 1. An additional implemented 500 hours salt spray resistance test affirms the possible operating temperature range from -25 °C up to +70 °C. The inside mounted 483 mm (19") profile rails (two pairs = 4 pieces) are galvanized and with height unit marking (countable from both directions). They are variable in depth and connected with additional depth support bars to realize extensive 483 mm (19") equipment installations. Furthermore there is an rotary profile hole structure inside. Each cabinet is equipped with a plinth (100 mm height) which offers additional space for cabling. The base of each cabinet is equipped with a sliding cable entry panel with rubber sealing as well as five PG cable screw inlets (4x PG21 + 1x PG48). An extensive portfolio of accessories for cable

management, shelves, etc. will help to meet many requirements in daily use.

- Blacha stalowa o grubości 1,5–2,0 mm
- Profile montażowe 483 mm (19") zamontowane na przedniej i tylnej stronie w szafie, galwanizowane
- Profile montażowe 483 mm (19") posiadają regulację głębokości i oznaczenie jednostki wysokości
- Drzwi przednie: Drzwi szklane, pojedyncze
- Głębokość: 600 mm
- Kolor: Jasnoszary, RAL 7035
- Nośność: 1500 kg
- Szerokość: 600 mm
- Typ szafy: Szafa przemysłowa
- Wysokość [U]: 24
- Stopień ochrony IP: IP55
- Zmontowana: tak

Zawartość opakowania

- Earthing wire set
- Installation set (screws, cage nuts, washers)

Logistyka						
	Liczba (sztuki)	Waga (kg)	Głębokość (cm)	Szerokość (cm)	Wysokość (cm)	cm³
Zewnętrzne opakowanie zbiorcze	1	86.00	65.00	65.00	135.00	570,375.00
Opakowanie wewnętrzne	1	86.00	65.00	65.00	135.00	570,375.00
Opakowanie jednostkowe	1	86.00	65.00	65.00	135.00	570,375.00
Netto bez opakowania	1	85.00	60.00	60.00	130.00	0.00

Więcej zdjęć

