Datasheet

DIGITUS USB-PS/2 Combo-KVM Switch

DS-23300-2
EAN 4016032429999



16-port Combo-KVM switch, 1 user, 16 PCs, IP function module slot

The high quality KVM switches with IP function (optional) are ideal for using in small to middle sized server rooms in which an access of the administrator must be guaranteed at any time from any place. They provide direct connection from a local console or even due to remote control over an existing internet connection. Due to the possibility to upgrade the firmware, they fit simply to all new conditions.

Combo-KVM Switch 1User,16PCs (each PS/2 or USB),

- Combo-KVM Switch 1User,16PCs (each PS/2 or USB),
- Full control under all OS, in BIOS level, during boot, or at Blue Screens
- resolution 1280X1024 at 60Hz
- Supports max. resolution up to 1920x1200 pixels
- Hot plug support
- Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error
- Autoscan (5 to 90 sec., selectable)
- Compliant to USB 2.0 specification
- Rack mountable
- IP function module slot
- Power Spec: AC 100-240V
- Power Consmption: 9W
- DC plug Size: 5.5*2.1mm

Package contents

- KVM switch
- 1x power adapter (9V1A)
- 1x rack mount bracket kit
- 1x User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	4	23.16	47.50	33.00	44.00	68,970.00
Packaging Unit Inside	1	5.79	47.50	15.50	22.00	16,197.50
Packaging Unit Single	1	5.79	43.20	15.50	4.40	2,946.24
Net single without Packaging	1	5.23	43.20	15.50	4.40	0.00

More images:



