

DIGITUS colored pigtails, LC/UPC Simplex, OM5, LSZH

DK-25332-02-5
EAN 4016032446576



FO pigtail set, 12 pcs., LC, MM OM5 50/125 μ loose buffer, color code DIN IEC 304, 2m

FO pigtail set, 12 pcs., LC, MM OM5 50/125 μ , loose buffer, color code DIN IEC 304, 2m

Future-oriented standards and high-end quality for your network.

- Simplex OM5 50/125 μ 2 m
- Operating temperature: -25 °C ... +80 °C

- Storage temperature: -20 °C ... +65 °C
- Zirconia ceramic ferrule
- Colored buffer, according to IEC 304 in the colors white, violet, turquoise, black, red, pink, orange, grey, green, yellow, brown, blue
- 12 pcs in package
- Loose buffer

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	160	10.94	23.00	23.00	12.00	6,348.00
Packaging Unit Inside	4	0.27	22.00	17.00	3.00	1,122.00
Packaging Unit Single	1	0.07	16.00	14.00	1.00	224.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00