

DIGITUS 4K HDMI Extender Set, HDBaseT™, 4K/60Hz, 70 m

DS-55503

EAN 4016032449003



4K HDMI Extender Set, HDBaseT, UHD 4K*2K@60Hz 70m over network cable (Cat 6, 6a, 7)

The Digitus 4K Extender Set, HDBaseT™, 4K/60Hz offers an extender solution of up to 70 m for the highest demands - both for high-resolution graphics and for absolutely smooth video playback. It transmits digital video and audio signals to a maximum length of up to 70 m. HDMI signals (4K, 60Hz) can be transmitted to up to 70 m using a CAT 6 network cable. RS232 control signals can also be transmitted bidirectionally. It consists of a transmitter as well as a receiver unit. The package also includes two bidirectional infrared units (sender, receiver), which can be used for the remote control of the connected input source.

Extends the maximum length for HDMI signals to up to 70 m using only a simple network cable between a transmitter and a receiver unit

- Extends the maximum length for HDMI signals to up to 70 m using only a simple network cable
- Extends 4K/60Hz video contents to up to 70 m with a CAT 6 cable
- Transmits HDMI, IR (bidirectional) and RS232 (bidirectional) signals
- Supports 4K (60Hz), 4096 x 2160p resolution
- Uses HDBaseT™ technology
- Transmits RS232 control signals (bidirectional)
- Supports CAT 6, CAT 6A, and CAT 7 network cables
- HDMI bandwidth: 18 Gbit/s (max.)
- Supports HDCP 2.2
- Integrated bidirectional IR interface - easy remote control of the input source
- Resolutions: 4K (60Hz), 4K (30Hz), 1080p, 1080i, 720p, 576p, 576i, 480p, 480i

- LED status indicator
- Supports: 3D, HDTV
- Supports CEC
- Supports Deep Color (24bit)
- Supports compressed audio signals such as DTS digital, Dolby digital (including DTS-HD and Dolby True HD)
- Supports uncompressed audio signals such as LPCM
- Metal housing
- Compact size, simple use and installation
- Power Supply: DC12V/2A
- Dimensions (1x unit): L 11.0 x B 8.7 x H 2.4 cm
- Weight (1x unit): 0.5 kg
- Color: Black
- HDTV Resolution max.: 4096 x 2160 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Category: CAT 6
- Distance: 70 m
- KVM: no
- KVM: no
- PoE (Power over Ethernet): no
- Video connection ports: HDMI

Package contents

- 1x HDMI Extender transmitter unit
- 1x HDMI Extender receiver unit
- 2x Power supply unit: DC 12V/2A
- 2x IR sender unit
- 2x IR receiver unit
- 2x RS232 connection cap

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	9.00	38.00	27.00	42.00	43,092.00
Packaging Unit Inside	1	0.90	24.00	17.60	8.00	3,379.20
Packaging Unit Single	1	0.90	24.00	17.60	8.00	3,379.20
Net single without Packaging	1	0.50	11.00	8.70	2.40	0.00

More images:

