

DIGITUS USB 2.0 serial adapter

DA-70167

EAN 4016032456308



USB 2.0 to serial Converter, DSUB 9M incl. USB A Cable 80cm

The DIGITUS® USB 2.0 serial adapter is a practical solution for serial connectivity. RS232 serial interfaces are no longer available on new hardware, so the DIGITUS® USB 2.0 serial adapter enables data exchange between a computer USB 2.0 port and peripheral devices with serial interfaces (COM port, RS232). These include, for example, weather stations, sensors, machine control systems, set-top boxes, gaming consoles, PDAs, scanners, modems, ISDN adapters and many other peripheral devices. The USB 2.0 serial adapter is downwardly compatible with USB 1.1 and enables adaptable baud rates of between 75 and 128,000 bits per second. The customizable PL2303GT chipset is compatible with all common operating systems and also supports power management and remote wake up. A separate power supply is not required, because the device is powered through the USB connection.

Provides a serial RS232 interface via USB 2.0

- Provides a serial RS232 interface via USB 2.0

- Meets the USB 2.0 standard
- Downward compatibility with USB 1.1
- Adaptable data transfer rates of between 75 and 128,000 bits per second.
- Supports remote wake up and power management
- Chipset: PL2303GT
- Customizable with the PL2303GT chipset
- 1× RS232 plug (Sub D 9-pole) / 1× USB A plug
- Interface: Full duplex
- Gilded contacts
- Incl. USB extension cable, approx. 80 cm
- Supports Windows 10, 8.1, 8, 7, Vista, XP, Mac OS X and Linux
- True 3.3V CMOS drive output and TTL input

Package contents

- USB serial adapter
- USB extension cable
- Driver CD

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	10.20	30.00	46.00	25.00	34,500.00
Packaging Unit Inside	1	0.10	10.00	14.00	5.00	700.00
Packaging Unit Single	1	0.10	10.00	14.00	5.00	700.00
Net single without Packaging	1	0.06	3.30	7.40	1.50	0.00

More images:

