
Datasheet

DIGITUS CAT 6A U/UTP slim patch cord

DK-1617-A-100S
EAN 4016032461760



CAT 6A U-UTP Slim patch cord, Cu, LSZH AWG 28/7, length 10 m, color grey


DIGITUS® slim patch cords are characterised by their small outer diameter and flexible sheath. Slim design enables versatile use in your network. Moreover, The DIGITUS® Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk (“NEXT”). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.


Enables flexible and space-saving cabling in your network

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Bending radius: 4D (outer diameter x 4)
- outer diameter: 3,65 mm
- Configuration: 1:1
- Category: CAT 6A
- Shielding: U-UTP, unshielded
- Length: 10 m
- Color: grey
- Jacket: LSOH
- Slim Version: yes
- Structure: 4 x 2 AWG 28/7, twisted pair


Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	7.20	32.00	50.00	21.00	33,600.00
Packaging Unit Inside	1	0.18	27.00	19.00	2.30	1,179.90
Packaging Unit Single	1	0.18	27.00	19.00	2.30	1,179.90
Net single without Packaging	1	0.16	17.00	17.00	2.30	0.00

More images:








DIGITUS
DK-1617-A-100S // CAT 6A U/UTP Slim Patch Cord
Router
Switch
Wall Outlet
Fiber Jack
Computer
Server