

DIGITUS 16 Port Gigabit PoE Switch, 19 Inch, Unmanaged, 2 Uplinks

DN-95347
EAN 4016032464334



Gigabit Ethernet PoE Switch 16-port PoE + 2 SFP, 380W PoE budget

The 16-Port Gigabit PoE+ Switch from DIGITUS® provides 16 x Gigabit RJ45 PoE+ ports along with 2 SFP uplink ports with 1 Gbps bandwidth each. The switch makes it possible to expand the existing network while transferring power and data to compatible devices using a single network cable. The PoE and PoE+ standards are supported by a total output of up to 380 watts and a maximum of 30 watts per port. Use the switch with devices such as access points, IP cameras or IP telephones with a power supply. Devices that support Power over Ethernet in line with the IEEE802.3af/at standard are detected automatically and supplied with power and do not require confirmation. The switch can be installed in 19-inch server cabinets and housing or used as a desktop version. Ideal for expanding home and business networks.

Gigabit Switch with Power over Ethernet (PoE) - Total output 380 W - Suitable for installation in 19-inch server cabinets

- Number of ports: 16 x 10/100/1000Mbps PoE+
- Uplink ports: 2 x SFP (2 x 1G)
- Auto-negotiation: Auto MDI/MDIX
- Backplane bandwidth: 36 Gbps
- Forwarding capacity: 26.78 Mpps
- CPU: 500 MHz
- RAM: 128 MB
- Buffer storage: 4.1 MB
- MAC addresses: 8K (auto-learning, auto-aging)
- Supports VLAN
- IEEE802.3x Flow Control for Full-Duplex
- Transfer method: Store and forward
- Total PoE output: 380W
- PoE output per port: 30W

- PoE+ standard: IEEE802.3at/af
- Integrated ventilator
- Operating voltage: 100 - 240 V AC, 50/60 Hz, integrated power adapter (IEC C13 plug for non-heating appliances)
- Operating temperature: 0 °C to 40 °C
- Operating humidity: 10% - 90% (non condensing)
- Storage temperature: -40 °C to +70 °C
- Dimensions: W 440 x D 290 x H 45 mm
- VLAN mode: Ports 1 - 14 are isolated from each other, VLAN ports can only access ports 15 - 18
- Normal mode: All ports can communicate with each other
- Number of ports: 16
- PoE Power budget: 380 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Industrial usage: no
- Installation type: 19 inch, Desktop
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: yes

Package contents

- 16-Port Gigabit Ethernet PoE+ Switch 2G SFP
- Power cord connection cable with coupling for non-heating appliances (IEC C13)
- Attachment material for 19-inch cabinets
- User manual
- Rubber feet

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3	13.60	54.00	31.00	41.00	68,634.00
Packaging Unit Inside	1	4.53	52.00	38.00	6.00	11,856.00
Packaging Unit Single	1	4.53	52.00	39.00	10.00	20,280.00
Net single without Packaging	1	3.52	44.00	30.00	4.50	0.00

More images:

