

# DIGITUS USB-C™ Docking Station with Wireless Video Extender, 8 Port

DA-70890

EAN 4016032465003



## 8 Port USB-C Dock with Wireless Video Extender 2x USB-A, HDMI, VGA, USB-C, 3.5mm, SD/MicroSD

The two-part DIGITUS® docking station transmits Full HD video signals to distances of up to 10 m. These video signals can be displayed on the HDMI® and VGA connection in parallel. Additionally, audio signals can be picked up via the existing 3.5 mm jack socket because a VGA cable cannot transmit any audio signals. The transmitter and receiver unit elegantly merge into one unit thanks to the integrated magnetic mount. When the connection is terminated, the docking station can be used as a video extender. The transmitter unit can be used within a 10-m radius of a notebook, tablet or smartphone and extends your device by two graphic interfaces, two USB A ports, one SD / MicroSD card reader, as well as one audio output. Periphery devices such as a mouse, keyboard, printer or USB sticks can be connected to the two USB A ports. The two memory card readers can be equipped with up to 2 TB. The 8-in-2 DIGITUS® docking station is the perfect solution for bridging small distances in offices or conference rooms with the most important interfaces for SOHO applications.

### USB-C™ docking station with wireless video transmission to HDMI™ / VGA Displays - 8 additional interfaces for your system

- Transmitter connections:
- 1 x USB-C™ host connection (notebook, tablet, smartphone): USB 3.0 SuperSpeed, 5 Gbps
- 2 x USB A connections: USB 3.0 (SuperSpeed, 5 Gbps, 5 V / 0.9 A)
- 1 x SD card reader: 2 TB max.
- 1 x MicroSD card reader: 2 TB max.
- Function button: Pairing, video: Start / stop, factory setting
- Receiver connections:
- 1 x HDMI® connection: Full HD (1920 x 1080p, 60 Hz)
- 1 x VGA connection: Full HD (1920 x 1080p, 60 Hz)
- 1 x USB-C™: Power supply for the receiver 10 W (5 V/2 A)
- 1 x audio: 3.5 mm jack socket (stereo output)
- Function button: Pairing, factory setting
- Transmission frequency: 5 GHz

- Supported operating systems: Windows 10/8/7, macOS® X 10.6 or higher, iPad OS®, Android 6.0 or higher, Google Chrome OS, Linux 2.6.14 or higher
- Power consumption receiver: 2.5 W (5 V / 500 mAh)
- Power consumption receiver: 3 W (5 V / 600 mAh)
- Dimensions transmitter: L 11.3 x W 5.8 x H 1.4 cm
- Dimensions transmitter: L 11.6 x W 6.1 x H 2.3 cm
- USB connection cable length: 80 cm (power supply)
- Length of transmitter connection cable: 13,5 cm
- Weight: 175 g
- Manufacturer's notice:
- Not all USB-C™ ports support all functions of the USB Type-C™ standard. Make sure that your notebook's USB-C™ port supports the DisplayPort Alternate Mode (DP Alt Mode).
- Not all USB-C™ ports support all functions of the USB Type-C™ standard. Make sure that your notebook's USB-C™ port supports the DisplayPort Alternate Mode (DP Alt Mode).
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- Housing: Aluminum
- LAN connector (RJ45): no
- Card reader: yes
- Number of audio ports: 1
- Number of display ports: 2
- Number of network ports: 0
- Number of USB A ports: 2
- Number of USB-C ports: 1
- Number of video ports: 2
- USB-C Products: yes
- Video connection ports: HDMI, VGA

### Package contents

- USB-C™ Dockingstation with Wireless Video Extender (Transmitter + Receiver)
- USB-C™ to USB A connection cable (power supply receiver)
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	30	7.15	42.30	73.00	28.50	88,005.10
Packaging Unit Inside	1	0.24	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.24	19.40	23.00	4.50	2,007.90
Net single without Packaging	1	0.21	6.10	11.60	3.70	0.00

**More images:**

