Datasheet

DIGITUS Ergonomic Stool / Standing Aid, Height-Adjustable with Gas Pressure Spring

DA-90422
EAN 4016032475279



Standing Stool, height-adjustable, black

Standing or sitting? Combine the two easily with the ergonomic office stool from DIGITUS®. This height-adjustable stool combines regular standing with relief for your legs. In addition, you also remain moving while seated because the chair is versatile. It can be rotated by 360° and the height can be adjusted from 63 to 88 cm to adapt optimally to the user's height or preferred application. Height adjustment is carried out by pressing a button, the integrated gas pressure spring supports you in the process. You can rock back and forth, do exercises or relieve your legs after standing for long periods of time. The height-adjustable standing and sitting chair makes it possible. Stay moving – even while seated!

Height-adjustable office stool for more dynamic sitting/standing

- Integrated gas spring - facilitates height adjustment
- Height adjustment: 63 - 88 cm
- Seat can be rotated by 180°
- Maximum load capacity: 125 kg
- Lifting cylinder diameter: 40 mm Lifting cylinder diameter: 40 mm
- Dimensions: W 33 x D 33 x H 63 - 88 cm
- Weight: 13 kg
- Manufacturer's notice:
- The base is unstable, which means the stool wobbles, tilts and rotates. Make sure that is securely positioned and held in place during use.
- This is not a stationary chair or stool.
- Style: Standig stool / stool

Package contents

- 1 x Ergonomic Stool / Standing Aid, Height-Adjustable with Gas Pressure Spring
- 1 x QIG


Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	11.00	41.00	71.00	20.00	58,220.00
Packaging Unit Inside	1	11.00	41.00	71.00	20.00	58,220.00
Packaging Unit Single	1	11.00	41.00	71.00	20.00	58,220.00
Net single without Packaging	1	9.00	33.00	33.00	63.00	0.00

More images:













DIGITUS
360°
30 - 51 cm
± 30°
max. 125 kg
Ergonomic Stool /
Standing Aid, Height-Adjustable
with Gas Pressure Spring


Ø330mm
± 180°
min500–max680mm
Ø40mm
Ø350mm